## SG

### **SIGHT GLASS**



#### **DESCRIPTION**

Sight glass has been developed for easy checking level of condensate accumulated in the bottom of compressed air filter howl.

On every casted aluminium filter housing there is a pre casted area where sight glass can be mounted after appropriate holes are drilled.

TECHNICAL DATA						
ТҮРЕ	SG					
Operating pressure	0 to 16 bar (0 to 232 psi)					
Operating temp.	1,5 to +65 °C (35 to 149 °F)					
Operating fluid	Air, water, oil					
Mass (kg)	0,010					
Material	PA12					
Dimensions (mm)	59,0 x 20,5 x 11,0					

# ES



#### **DESCRIPTION**

ES series expansion silencers are designed for efficient noise reduction at variety of applications where compressed air is expanded/depresurised to ambient pressure.

### **EXHAUST SILENCER**

TECHNICAL DATA						
Туре	Connection	Operating pressure	Operating temperature	Dimensions [mm]		
				Ø	h	
ES 06050	1/4"	0-13 bar	1,5 to +65°C	51	69	
ES 14050	3/8"			51	127	
ES 12075	1/2"			75	131	
ES 22075	3/4"			75	231	
ES 22090	1"			90	231	
ES 32090	11/4"			90	333	
ES 32140	11/2"			140	336	
ES 45140	2"			140	462	